



Interface Qualification for a Store-and-forward InterAct Messaging Interface

BOX For SWIFTNet Conformance Statement

Table of Contents

1	General Information	3
1.1	Supplier	3
1.2	Product Information	3
1.3	Conformance Testing Environment.....	3
1.4	Operational Environment	3
1.5	Customer Implementation Environment	4
1.6	Packaging Statement	4
1.7	Integration Support	4
2	Conformance Requirements	5
2.1	Messaging Interface Features	5
2.1.1	General Features.....	5
2.1.2	Security Features	5
2.1.3	Messaging Interface Application Support.....	6
2.1.4	Operational Features	6
2.1.5	RMA Management.....	7
2.1.6	Application Service Profile	7
2.2	Store-and-forward Features.....	8
2.2.1	General Features.....	8
2.2.2	Sequence of Transmission/Delivery.....	8
2.2.3	System Messages	9
2.2.4	Delivery Management.....	9
2.3	InterAct Features	9
2.3.1	Message Processing Features.....	9
2.3.2	Message Distribution Features	10
2.3.3	Copy Features	10

1 General Information

1.1 Supplier

Full name of the organisation that has registered this interface product and the name of the author of this Conformance Statement.

Organisation	INTERCOPE GmbH (Legal: Interscope International Communications Products Engineering GmbH)
Author	Jens Huser
Date	May 2011

1.2 Product Information

The name and version numbers of the interface product to which this qualification and conformance claim applies.

Product Name	BOX For SWIFTNet
Product Version Number	V3R11

1.3 Conformance Testing Environment

The hardware platform and software environment in which this interface product's conformance is validated.

Hardware Platform on which product was tested	Dell PC Intel Core 2, 3 GHz, 4 GB
Software Platform on which product was tested	Linux SLES 10 Database: DB2 v9 Other: MQ/Series v7, Java 1.5

1.4 Operational Environment

If the environment for which you want to claim and guarantee conformance is not identical to the environment in which conformance was validated, please specify the hardware platform(s) and/or software platforms for which this product's performance is guaranteed.

Hardware Platform on which product is guaranteed	IBM System z SUN IBM p-series PC
Software Platform on which product is guaranteed	Solaris AIX Windows Linux z/Linux z/OS-USS

1.5 Customer Implementation Environment

The hardware platform and software environment in which this interface product's customer implementation is defined (as required to achieve full qualification after an interim qualification).

Hardware Platform on which product was implemented	
Software Platform on which product was implemented	

1.6 Packaging Statement

Explains how this product is packaged.

The main possibilities are:

- *The product is a messaging interface only if the main purpose is to exchange messages/messages between back office applications and SWIFT.*
- *The product is integrated with another if the product offers other functionality such as connectivity to other external networks or the product is also a business application that creates and processes messages and files.*
- *The communication interface used by the product.*
- *The Relationship Management Application (RMA) used by the product.*
- *The security administration interface used by the product. For example, the management of security endpoints and its roles by security officers can be done by the product itself and/or by using SWIFTNet Online Operations Manager or another product.*

Other variations are possible. If used, these should be described below.

Product is a messaging interface only	No
Product is integrated with another (which)	Messaging Interface is part of BOX For SWIFTNet
Communication Interface	SWIFT Alliance Gateway
RMA Interface	BOX For SWIFTNet
Security Administration	Alliance Web Station
Other	BOX For SWIFTNet includes Backoffice integration capabilities

1.7 Integration Support

If not integrated how does this product link to user client or server products? Does it use the Message Queue Host Adapter or Remote API Host Adapter as specified by SWIFT? Does it use a proprietary or other industry standard solution?

MQHA	To SAG
RAHA	-
Other	Internal Interface/Protocol to BOX For SWIFTNet

2 Conformance Requirements

The conformance requirements for a store-and-forward InterAct messaging interface for SWIFTNet release 7.0 are specified in the corresponding interface specifications. A store-and-forward InterAct messaging interface for SWIFTNet release 7.0 must support the mandatory items referred to in the messaging interface specifications and any of the additional optional items.

The tables below identify the mandatory and optional elements that a store-and-forward InterAct messaging interface product may support. Please indicate for each whether your application supports and/or requires the elements, by entering the appropriate response in each of the columns on the right.

- Column 1 identifies the feature.
- Column 2 contains references to notes which describe the feature in more detail and where appropriate gives reference to the specification source.
- Column 3 describes whether the feature is Mandatory or Optional.
 - A Mandatory feature must be available for all users of the product.
 - An Optional feature, if implemented, is also subject to qualification.
- Column 4 is ticked "Y" or "N" to indicate support of the feature.

2.1 Messaging Interface Features

2.1.1 General Features

Feature	Note	M/O	Sup
Application identification within ProductList	A.1	M	Y
Usage of E2EControl for indication of PDE	A.2	M	Y
Provide client and server functionality	A.3	M	Y
Usage of enhanced errors	A.4	O	Y

Notes

- A.1 The messaging interface identifies itself in the ProductList. It also provides the ability for registered applications to use the ProductList within messages created by those applications or the messaging interface adds the ProductList when it identifies that an application is connected to the messaging interface.
- A.2 E2EControl must be used to identify the message for which possible duplicate information is to be provided.
- A.3 The client and server primitives from the communication interface must be used so that the messaging interface can play the role of client and of server in an efficient way.

This requires following the order of primitives to be sent and depends on the features offered by the communication interface.

- A.4 Enhanced errors are used by the messaging interface when the ErrorMode is set appropriately.

2.1.2 Security Features

Feature	Note	M/O	Sup
Access control	B.1	M	Y
Audit log	B.2	M	Y
Security officer	B.3	O	Y
Access control using 4-eyes principle	B.4	O	Y
Usage of SWIFTNet Link security contexts	B.5	M	Y
Renew rarely used SWIFTNet Link security contexts	B.6	M	Y
Local authentication (LAU) between communication interface and messaging interface if on different hosts for messages	B.7	O	Y

Interface Qualification Programme

LAU between communication interface and messaging interface if on different hosts for files	B.8	O	Y
Signature processing	B.9	M	Y

Notes

- B.1 Access to the messaging interface must be controlled. Updates in configuration information must be done by a user identified in a login process by providing a user name and password or equivalent methods.
- B.2 The audit log allows analysis of who changed what when. It also logs attempts to login by a user.
- B.3 Special users that can access and update security related information. Examples of security related updates are
- Adding, deleting, modifying users
 - Resetting passwords
- B.4 Two different users have to agree with a change before it is applied.
- B.5 SWIFTNet Link security contexts must be useable by entitled entities only. The implementation depends on the features offered by the communication interface.
- B.6 If a certificate is not used regularly, there is a risk that it will become invalid or expire. Once invalid or expired, the certificate will no longer be able to be renewed and must be recovered.
- B.7 This applies to the message protocol between communication interface and messaging interface.
- B.8 This applies to messages sent from/to the communication interface.
- B.9 The messaging interface must properly sign traffic it sends to SWIFT. Properly signing means to select the signature format (Crypto or SignatureList), and to select what is signed (what DigestRef to add). What is signed depends on the service and request type.

2.1.3 Messaging Interface Application Support

Feature	Note	M/O	Sup
Route incoming traffic to the correct business application	C.1	M	Y
Forward received signatures	C.2	O	Y
Forward own signatures	C.3	O	Y
Availability of messaging interface without connectivity to SWIFT	C.4	O	Y
Provide messaging interface processing information	C.5	M	Y
Provide SWIFTNet processing information	C.6	O	Y

Notes

- C.1 This routing can be based on various parameters taken from the received data. At a minimum, routing must be possible on the Service and RequestType taken from the RequestHeader or FileRequestHeader information.
- C.2 The signatures on data received can be made available to business applications requiring them.
- C.3 Ability to request a return of signatures on data sent and making them available to business applications requiring them.
- C.4 This feature allows business applications to send and receive messages/files even if the messaging interface is not connected via the communication interface to SWIFT. The messaging interface is a kind of hub between the business application and SWIFT.
- C.5 The most important processing information that can be passed consists of the verification result of the signatures. The minimum requirement is to allow routing the message/file based on the verification result of the signature.
- C.6 The processing information is related to non-repudiation, references added by SWIFT, routing information, copy related information such as the copy status. The business application can receive all information or a configured subset of processing information to be received.

2.1.4 Operational Features

Feature	Note	M/O	Sup
Traffic logging	D.1	O	Y
Unattended operations	D.2	O	Y

Backup/restore of messaging information	D.3	O	Y
Backup/restore of configuration data	D.4	O	Y

Notes

- D.1 Separate log from the actual messages/files sent or received is available for event analysis.
D.2 The ability to use a messaging interface with minimal operator intervention.
D.3 The ability to backup and restore messaging data (messages or files).
D.4 The ability to backup configuration data. Depending on the design it can be several types of backup/restore related to a coherent set of data of one or more subsystems.

2.1.5 RMA Management

Feature	Note	M/O	Sup
Check authorisation-to-send	E.1	O	Y
Check authorisation-to-receive	E.2	O	Y
Import RMA Authorisations	E.3	O	Y
RMA deployment – RMAChecked	E.4	O	Y
Configure local check mode in RMA trial period	E.5	O	Y
RMA deployment – reports	E.6	O	Y

Notes

- E.1 The messaging interface checks the existence of an authorisation-to-send for the request that will be sent on the service.
E.2 The messaging interface checks the existence of the authorisation-to-receive for the request that is received on the service.
E.3 The messaging interface can import RMA authorisations.
E.4 The messaging interface indicates the usage of the authorisation-to-send in the RequestControl, FileRequestControl and FileResponseControl as appropriate.
E.5 The local configuration changes the behaviour of the checking of RMA authorisations-to-send and authorisations-to-receive during the trial period.
When check mode is on and a check fails, the traffic is stopped. When check mode is off and a check fails, the traffic is not stopped.
E.6 The messaging interface provides information about the usage of authorisations for traffic sent and received.
The report can be integrated within traffic investigation reports or can be integrated within audit log reports.

2.1.6 Application Service Profile

Feature	Note	M/O	Sup
Application Service Profile Package Import	F.1	O	Y
Application Service Profile Package Usage	F.2	O	Y

Notes

- F.1 The messaging interface is be able to import the package and apply the definitions of the application service profiles.
F.2 An application service profile contains a set of parameters as decided by the Service Administrator during the definition of the service. The application service profile is used by messaging interfaces and applications to correctly send and receive traffic for that service.

2.2 Store-and-forward Features

2.2.1 General Features

The table below lists the general features required by messaging interfaces supporting store-and-forward.

Feature	Note	M/O	Sup
Start a Session on a Queue	G.1	M	Y
Stop a Session on a Queue	G.2	M	Y
Monitor Queues	G.3	M	Y
Generic Queues for Requests and Messages	G.4	M	Y
Support of System Recovery	G.5	M	Y
Send Y-Copy Authorisation or Refusal	G.6	O	Y
Exchanging messages over store-and-forward requires at least one of the following to be supported:	G.7	M	Y
Pull mode	G.8	O	Y
Push mode	G.9	O	Y
Support of version 6 queue sessions	G.10	O	Y
Support of Cold Start	G.11	M	Y

Notes

- G.1 This performed by opening an output channel.
- G.2 This is performed by closing an output channel.
- G.3 The ability of the messaging interface to monitor queues.
- G.4 This supports the single window concept, where different business services can use the same queue. Generic queues can simplify the MRR setup.
- G.5 A SWIFTNet store-and-forward system recovery is done when the active site becomes inoperable for some reason. In this case, some data previously sent to SWIFT may need to be resent. The amount of data depends on the replication status of store-and-forward prior to the incident that caused the active site to stop.
- G.6 This is mandatory for messaging interfaces used by third-party organisations that offer Y-Copy services. The authorisation itself is always created by a business application using the messaging interface.
- G.7 Store-and-forward interface must choose one of the following modes:
- G.8 The product may use Pull mode to fetch messages from its queues, or
- G.9 The product may use Push mode to receive messages from its queues automatically.
- G.10 An optional method defined in previous versions defined by acquiring queues. This method does not allow for reception of distributed messages.
- G.11 The procedure for restarting the operations after a cold start will use the available features of the interface. Accurate documentation is essential to guide the user so that recovery from the cold start is as easy as possible. This documentation must be available at the time of cold start.

2.2.2 Sequence of Transmission/Delivery

Feature	Note	M/O	Sup
Support of Output Channels	H.1	M	Y
Support of Input Channels	H.2	M	Y
Queue Sharing	H.3	O	Y

Notes

- H.1 The support of output channels consists of using the primitives for output channels and the monitoring of their state through the event handling.

- H.2 The support of input channels consists of using the primitives for input channels in order to send messages.
- H.3 Queue sharing is done by opening several output channels on the same queue.

2.2.3 System Messages

Feature	Note	M/O	Sup
Create System Messages	I.1	O	Y
Create System Report Requests	I.2	O	Y
Send System Messages	I.3	M	Y
Receive System Messages	I.4	M	Y
Process Received System Messages	I.5	O	Y

Notes

- I.1 Creation of system messages can be done by a business application using the messaging interface or by the messaging interface itself.
- I.2 The ability of the messaging interface to create report requests.
- I.3 The ability of the messaging interface to send system messages.
- I.4 The ability of the messaging interface to receive system messages.
- I.5 This can be done by a business application using the messaging interface or by the messaging interface itself.

2.2.4 Delivery Management

Feature	Note	M/O	Sup
Acknowledge Receipt	J.1	M	Y
Receive Delivery Notifications	J.2	M	Y
Receive Notifications of Authorisation or Refusal	J.3	M	Y
Reconcile Undelivered Traffic Reports	J.4	O	Y

Notes

- J.1 The messaging interface acknowledges receipt after having safe stored the data it receives. This requires persistent storage.
- J.2 The ability of the messaging interface to receive delivery notifications.
- J.3 The ability of the messaging interface to receive notifications of authorisations or refusal.
- J.4 The ability of the messaging interface to reconcile undelivered traffic reports.

2.3 InterAct Features

2.3.1 Message Processing Features

The table below lists the general features required by messaging interfaces supporting InterAct.

Feature	Note	M/O	Sup
Send messages – 4eyes	K.1	O	Y
Send messages	K.2	M	Y
Receive messages	K.3	M	Y
Use system messages as delivery notifications	K.4	O	Y
Prepare messages	K.5	O	Y
Correct messages	K.6	O	Y

Select 1 or more copy destinations	K.7	M	Y
------------------------------------	-----	---	---

Notes

- K.1 This is a step in the flow of sending files where another operator is involved. This can be implemented by business applications.
- K.2 The client part of the communication interface primitives for sending InterAct is invoked.
- K.3 The messages are received from the server part of the communication interface.
- K.4 Delivery notifications as system messages contain the FileRequestHeader as context information.
- K.5 Allow message entry. This can be done by business applications.
- K.6 This can be done by business applications. The messaging interface must then be able to route messages that failed to be sent to a business application for correction, or to provide the necessary information to identify the failed messages.
- K.7 This is mandatory for the messaging interface used to indicate which copy destination a file is to be copied to. This selection is from a list of possible third parties for that service (These can be taken from the application service profile, if supported). This can also include multiple destinations. *If messaging interface is deployed to corporate users only, then this functionality is optional.*

2.3.2 Message Distribution Features

The table below lists the distribution features that messaging interfaces supporting InterAct may use. Complete this section if your messaging interface supports these distribution features.

Feature	Note	M/O	Sup
Send message distribution request	L.1	O	Y
Receive distributed message	L.2	M	Y

Notes

- L.1 This is the creation of a message distribution request.
- L.2 This is the same as any other messages, except for the handling of the RecipientList.

2.3.3 Copy Features

The following table lists the features required by InterAct messaging interfaces supporting third party services.

Feature	Note	M/O	Sup
Act as a copy destination for T-Copy	M.1	O	Y
Act as a copy destination for Y-Copy	M.2	O	Y
Act as a copy destination for Y-Copy in TCOPYFallback	M.3	O	Y

Notes

- M.1 This is mandatory for the messaging interface used by a copy destination for processing copied messages. T-Copy is a service where the file is delivered to the receiver without any dependency of the copied information.
- M.2 This is mandatory for the messaging interface used by a copy destination for processing copied messages. When the service is Y-Copy, the message is copied to the third party. The third party must authorise or refuse the message to be delivered to the receiver. The third party may refuse the delivery of the message to the receiver, in which case, the sender is informed via a refusal notification message.
- M.3 This is mandatory for the messaging interface used by a copy destination for processing copied messages with CopyState=TCOPYFallback.

Legal Notices

Copyright

SWIFT © 2011. All rights reserved.

You may copy this publication within your organisation. Any such copy must include these legal notices.

Confidentiality

This publication contains SWIFT or third-party confidential information. Do not disclose this publication outside your organisation without the prior written consent of SWIFT.

Disclaimer

The information in this publication may change from time to time. You must always refer to the latest available version on www.swift.com.

Translations

The English version of SWIFT documentation is the only official and binding version.

Trademarks

SWIFT is the trade name of S.W.I.F.T. SCRL. The following are registered trademarks of SWIFT: SWIFT, the SWIFT logo, Sibos, SWIFTNet, SWIFTReady, and Accord. Other product, service, or company names in this publication are trade names, trademarks, or registered trademarks of their respective owners.